



# GFM

FOLDING FLAIL



[www.lipa-srl.it](http://www.lipa-srl.it)  
[info@lipa-srl.it](mailto:info@lipa-srl.it)

65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170

# GFM

## FOLDING FLAIL




### STANDARD EQUIPMENT

- three-point attachment II and III cat.
- rear rubber protection
- front protection with galvanised and rubber chains
- support feet
- gearbox without inner freewheel
- cardan shaft with freewheel
- cardan protection boot
- rotor with toothed hammers
- oversized hammer supports
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear hood opening for inspection
- double-acting pistons for horizontal opening
- special powder or liquid painting (primer and enamel)



The GFM flail is an ideal tool for working on large flat and hilly surfaces, at airports and on cultivated and uncultivated land. It has a double attachment, front and rear. This reversibility means being able to maximise its performance and allows a choice of processing according to requirements.

Mod.			 Kg	 (Hp-kw) *	 (g/min.)		 D. Rotor	
<b>GFM-450</b>	4500	3000	2500	185-136	1000	2x16	245	2x5
<b>GFM-550</b>	5500	3000	2700	185-136	1000	2x20	245	2x5

\* The horse power shown in the table is indicative and represents the power required by the Flail for operation.

### ACCESSORIES ON REQUEST

1. Pair of side skids



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)