



TLA-P

MOVEABLE FLAIL

(heavy type)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLA-P

MOVEABLE FLAIL









(heavy type)



STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- support feet
- gearbox outside the flail mower with internal freewheel
- single homokinetic cardan
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- pair of side skids
- oversized hammer supports
- rear hood opening for inspection
- double acting piston for lateral movement with flow regulator
- double acting piston for inclination with D.E. lock valve with flow regulator
- double lower attachment on the stand
- levelling joint
- special powder or liquid painting (primer and enamel)

The TLA-P flail is an ideal piece of equipment for the shredding of bushes near ditches, embankments, vineyards and orchards. The available boom allows a variety of uses: internally as a common mulcher, laterally for work near the end of the field or ditches and in a vertical position for the pruning of hedges.

Mod.	 (B/H/Z) B	 L	 Kg	 (Hp-kw) *	 (g/min.)	 D. Rotor	 Ø	
TLA-P 200	2700/960/970	2000	1150	70-52	540	13	180	5
TLA-P 220	2940/960/970	2240	1200	80-59	540	15	180	5
TLA-P 250	3100/960/970	2540	1300	100-73	540	17	180	5

* the horsepower shown in the table are indicative and express the capacity required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Galvanised and rubber chains to replace the strips
2. Rubber protection on strips

