



TLB-FF

HYDRAULIC FORESTRY MULCH

(for skid steer)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLB-FF

HYDRAULIC FORESTRY MULC

(for skid steer)



STANDARD EQUIPMENT

- skid steer attachment
- frame in sheet metal with DOMEX high yield index
- internal reinforcement with Hardox wear-resistant PLATE
- rear and front rubber protection
- hydraulic engine with drainage
- anti-cavitation valve
- rotor with two-way retractable hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- pair of side skids
- hood opening piston
- special powder or liquid painting (primer and enamel)

The TLB-FF hydraulic forestry flail for skid steers is a robust and versatile tool suitable for the shredding of grass, reeds and bushes up to a maximum of 9/10 cm in diameter. Fits skid steers with a minimum power of 50 Hp (22 Kw).

| Mod. | | | | | | | | | |
|------------|--------------|------|-----|----------|--------|------------|----------|-----|---|
| | (B/H/Z) | L | Kg | (g/min.) | L/1' * | Press. BAR | D. Rotor | | |
| TLB-FF 120 | 1408/928/690 | 1206 | 450 | 2300 | 55/60 | 220/250 | 21 | 352 | 4 |
| TLB-FF 130 | 1558/928/690 | 1369 | 475 | 2300 | 60/70 | 220/250 | 24 | 352 | 4 |
| TLB-FF 150 | 1723/928/690 | 1532 | 500 | 2300 | 80/90 | 220/250 | 27 | 352 | 4 |

* The litres shown in the table are indicative and express those required by the mulcher for its operation.

ACCESSORIES ON REQUEST

1. Solenoid valve kit
2. Surcharge fixed Cutting ax and sharp hammer rotor:
 - TLB-FF 120 QT 39
 - TLB-FF 130 QT 44
 - TLB-FF 150 QT 51

