





www.lipa-srl.it info@lipa-srl.it 65010 Spoltore (PE) - Italy Via Castellani (ang. Via Mare Adriatico) Tel. +39 085 4971431 Fax +39 085 4973170







STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- stabiliser foot
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with smooth hammers
- belt transmission
- rear heightadjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- special powder or liquid painting (primer and enamel)

The TLB Flail is a piece of equipment used for the shredding of grass and small branches, has a three-point attachment and is applicable to crawler and wheeled tractors of Cat II and III.

Mod.	(B/H/Z)		Kg	(Hp-kw) *	(5) (g/min.)	2	Ø D. Rotor	
TLB-120	1340/850/750	1240	250	20/30-15/22	540	12	108	2
TLB-130	1440/850/750	1340	270	20/30-15/22	540	13	108	2
TLB-140	1540/850/750	1440	280	25/30-18/22	540	14	108	3
TLB-150	1640/850/750	1540	290	25/30-18/22	540	15	108	3
TLB-160	1740/850/750	1640	310	25/30-18/22	540	16	108	3

* the horsepower shown in the table are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

- 1. Pair of side skids
- 2. Rear galvanised harpoons
- **3.** Front rubber protection on the strips







