



# TLBA

**MOVEABLE FLAIL**  
(light type)



[www.lipa-srl.it](http://www.lipa-srl.it)  
[info@lipa-srl.it](mailto:info@lipa-srl.it)

65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170

# TLBA

## MOVEABLE FLAIL

(light type)



### STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- stabiliser foot
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with smooth hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- pair of side skids
- double acting piston for lateral movement with flow regulator
- double acting piston for angular inclination with D.E. lock valve with flow regulator
- levelling joint
- special powder or liquid painting (primer and enamel)

The TLBA Flail is a piece of equipment used for the shredding of shrubs near ditches, banks, orchards and roadside edges. The available boom allows a variety of uses: internally for agricultural use, laterally for work near the end of the field or ditches and in a vertical position for the pruning of hedges.

Mod.				 (Hp-kw) *	 (g/min.)	 D. Rotor		
TLBA-140	1560/1000/1800	1440	370	25/30-18/22	540	14	108	3
TLBA-150	1660/1000/1800	1540	390	25/30-18/22	540	15	108	3
TLBA-160	1760/1000/1800	1640	410	25/30-18/22	540	16	108	3

\* The horsepower shown in the table are indicative and express the power required by the flail for its operation.

### ACCESSORIES ON REQUEST

1. Gearbox outside the mulcher
2. Surcharge single homokinetic cardan
3. Double lower attachment on the stand
4. Rubber protection on strips



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)