



# TLBE-S

## HYDRAULIC MULCHING HEAD

(for excavator)



[www.lipa-srl.it](http://www.lipa-srl.it)  
[info@lipa-srl.it](mailto:info@lipa-srl.it)

65010 Spoltore (PE) - Italy  
Via Castellani (ang. Via Mare Adriatico)  
Tel. +39 085 4971431 Fax +39 085 4973170

# TLBE-S

## HYDRAULIC MULCHING HEAD

(for excavator)



### STANDARD EQUIPMENT

- attachment saddle (25kg)
- saddle adjustment rail
- hydraulic gear motor group 3
- anti-cavitation valve
- belt transmission
- rotor with toothed hammers
- internal counterframe
- double series of counter-elements
- front protection with galvanised and rubber chain
- rear rubber protection
- pair of skids
- rear height-adjustable roller with scraper
- special powder or liquid painting (primer and enamel)

The TLBE-S mulching head is ideal for the mulching of grass, reeds and bushes up to a maximum of 7/8 cm in diameter, near ditches, embankments and on all steep slopes. Fits excavators with weight from 5T.

Mod.									
	B	L	* Kg	(g/min.)	L/1* *	Press. BAR		D. Rotor	
<b>TLBE-S 90</b>	1050	940	320	2300	45/55	220/250	10	140	3
<b>TLBE-S 100</b>	1150	1040	330	2300	50/60	220/250	10	140	3
<b>TLBE-S 110</b>	1250	1140	350	2300	60/70	220/250	11	140	3
<b>TLBE-S 120</b>	1350	1240	370	2300	60/70	220/250	12	140	3

\* The data shown in the table are indicative, refer to the weight of the mulching head without saddle and the litres are those required by the shredding head for its operation.

### ACCESSORIES ON REQUEST

1. Oscillating attachment (50kg)
2. Oversized hammer supports
3. Saddle fixing pins
4. Surcharge valve block with flow and limiter regulator
5. Swivel unit
6. There is an additional cost for customising of the saddle



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)