



TLC
FLAIL
(heavy type)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLC

FLAIL (heavy type)



STANDARD EQUIPMENT

- three-point hitch
- rear rubber protection
- front protection with galvanised strips
- stabiliser foot
- gearbox with internal freewheel
- cardan shaft
- cardan protection boot
- rotor with toothed hammers
- belt transmission
- rear height-adjustable roller with scraper
- internal counterframe
- series of internal counter-elements
- rear hood opening for inspection
- special powder or liquid painting (primer and enamel)


The TLC flail is a tool used for the shredding of grass and branches, for the pruning of vineyards, orchards and olive groves. It has a three-point hitch and an openable hood that facilitates inspection. It adapts to any tracked or wheeled tractor.

| Mod. | | | | | | | | |
|----------------|--------------|------|-----|-------------|-----|----|-----|---|
| TLC-120 | 1360/800/900 | 1240 | 400 | 30/35-22/26 | 540 | 8 | 160 | 3 |
| TLC-130 | 1460/800/900 | 1340 | 420 | 35/40-26/29 | 540 | 9 | 160 | 3 |
| TLC-140 | 1560/800/900 | 1440 | 450 | 40/45-29/33 | 540 | 10 | 160 | 3 |
| TLC-150 | 1660/800/900 | 1540 | 460 | 45/50-33/37 | 540 | 10 | 160 | 3 |
| TLC-160 | 1760/800/900 | 1640 | 490 | 50/55-37/40 | 540 | 11 | 160 | 4 |
| TLC-180 | 1960/800/900 | 1840 | 530 | 55/60-40/44 | 540 | 12 | 160 | 4 |
| TLC-200 | 2120/800/900 | 2000 | 580 | 60/65-44/48 | 540 | 13 | 160 | 4 |
| TLC-220 | 2360/800/900 | 2240 | 600 | 65/70-48/51 | 540 | 15 | 160 | 4 |

* the horsepower shown are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Pair of side skirts
2. Oversized hammer supports
Sizes 120-150
Sizes 160-220
3. Front rubber protection on the strips



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)