



TLE-FS/FM

FORESTRY HYDRAULIC MULCHING HEAD
(for excavator)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLE-FS/FM

FORESTRY
HYDRAULIC
MULCHING HEAD
(for excavator)



STANDARD EQUIPMENT

- DOMEX sheet metal body
- internal reinforcement in HARDOX
- attachment saddle (55 kg)*
- saddle adjustment rail
- hydraulic piston engine with external drainage
- anti-cavitation valve
- belt transmission
- series of internal counter-elements
- forestry rotor with two-way retractable hammers
- front protection with galvanised and rubber chain
- double front and rear chain protection
- pair of skids with HARDOX reinforcement
- special powder or liquid painting (primer and enamel)

The TLE-FS/FM mulching heads with retractable or fixed hammer are suitable for the shredding of prunings and branches up to a maximum of 15cm in diameter. The TLE-FS mulching head is applicable to excavators weighing between 6t and 8t. The TLE-FM shredding head is applicable to excavators weighing between 8t and 10t.

Mod.											
light											
TLE-FS 70	984x550x920	714	420	2300	60/70	220/250	12	370	23	350	3
TLE-FS 90	1147x550x920	877	520	2300	70/80	220/250	15	370	29	350	3
medium											
TLE-FM 100	1314x550x920	1043	630	2300	80/90	220/250	18	370	33	370	3
TLE-FM 110	1477x550x920	1206	690	2300	90/100	220/250	21	370	39	370	4

* The data refer to the weight of the mulching head without saddle and the litres shown are indicative and express the flow rates required by the shredding head for its operation.

ACCESSORIES ON REQUEST

1. Saddle fixing pins
2. Rotor with fixed hammers (ax and sharp)
3. Flow regulator valve with solenoid valve
4. There is an additional cost for customising of the saddle



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)