



TLT-FM

FORESTRY MULCHER

(medium type)



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLT-FM

FORESTRY MULCHER

(medium type)



STANDARD EQUIPMENT

- DOMEX sheet metal body
- internal counterframe in HARDOX wear-resistant sheet metal
- triple series of welded internal counter-elements
- three-point hitch
- double lower attachment on the stand
- front protection with double row of galvanised chains
- support feet
- oversized gearbox with internal freewheel
- 3/4 Z6 cardan shaft suitable for 120/140 HP
- V80 cardan joint
- cardan protection boot
- belt transmission
- rotor with toothed hammers
- oversized hammer supports
- side skids with HARDOX wear-resistant sheet reinforcement
- rear hood that can be opened with a roller of D. 170
- two double-acting pistons for hood opening
- special powder or liquid painting (primer and enamel)

The TLT-FM fixed forestry mulcher is an interchangeable multi-purpose piece of equipment intended for processing in agriculture such as the clearing of orchards and tidying the landscape, in forestry such as for the mulching of brush and undergrowth and light thinning. It has an openable hood that facilitates reverse processing, increasing the ability to convey the processed material.

Mod.								
	(B/H/Z) B	L	Kg	(Hp-kw) *	(g/min.)	D. Rotor	D. Rotor	D. Rotor
TLT-FM 160	1910x1100x1300	1640	730	45-50	540	11	160	5
TLT-FM 180	2110x1100x1300	1840	820	55-60	540	12	160	5
TLT-FM 200	2270x1100x1300	2000	910	60-65	540	13	160	5
TLT-FM 220	2510x1100x1300	2240	1000	70-75	540	15	160	5

* the horsepower shown are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Rear galvanised harpoons



The technical data, illustrations and features are indicative and do not commit the manufacturer (put at the end of the page)