



UFM

FORESTRY FLAIL



www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

UFM









FORESTRY FLAIL



STANDARD EQUIPMENT

- three-point hitch cat. II and III
- DOMEX sheet metal body
- internal subframe with HARDOX wear-resistant plate
- series of internal counter-elements
- front and rear protection with galvanised chains
- support foot
- gearbox without internal freewheel
- cardan shaft with freewheel
- cardan protection boot
- rotor with two-way retractable hammers
- belt transmission
- pair of skids with HARDOX wear-resistant sheet metal reinforcement
- rear hood with hydraulic opening
- third hydraulic point
- special powder or liquid painting (primer and enamel)

The UFM flail is an ideal piece of equipment in forestry for tasks involving the removal of minor paths in woods, of fire paths, for the shredding of forest residues and timber. in agriculture for the work of clearing orchards, the shredding of branches, using rear and front mounting.

Mod.			 Kg	 (Hp-kw) *	 (g/min.)		 D. Rotor	
UFM-180	1890	2230	1750	136-100	1000	36	470	4
UFM-225	2290	2630	1980	160-118	1000	45	470	4

* the horsepower shown in the table are indicative and express the power required by the flail for its operation.

ACCESSORIES ON REQUEST

1. Manual lowering stand
UFM-180
UFM- 225

