

TLE-FJ

FORESTRY HY**DRAULIC** MULCHING HEAD

(for midi-**ex**cavator**)**

Made in Italy

www.lipa-srl.it
info@lipa-srl.it

65010 Spoltore (PE) - Italy
Via Castellani (ang. Via Mare Adriatico)
Tel. +39 085 4971431 Fax +39 085 4973170

TLE-FJ

industrial line





The mulching head TLE-FJ is a light, high-performance forestry equipment. It is compact in size and perfect for mulching grass, reeds and bushes up to a max diameter of 7/10, near ditches, banks and in all steeply sloping terrains. It is suitable for excavators weighing from 5 t to 8 t.

STANDARD EQUIPMENT

- attachment saddle (25 kg)
- hydraulic gear motor group 2 (sz.100 group 3) with integrated anti-cavitation valve
- belt transmission
- rotor with fixed hammers
- internal counterframe
- double series of counter-elements
- front and rear protection with galvanized chains
- cylinder for hood opening
- pair of skids
- special powder or Liquid painting (primer and enamel)

Mod.	B	L	Kg *	(g/min.)	L/1' *	Press. BAR		Ø rotor mm	
TLE-FJ 70	907	717	370	2300	60/70	190/220	21	220	3
TLE-FJ 90	1107	917	420	2300	70/80	200/220	24	220	3
TLE-FJ 100	1207	1017	450	2300	80/90	220/250	27	220	3

* The data shown in the table are indicative, the weight refers to the mulching head without saddle and the litres are those required by the head for its operation

ACCESSORIES ON REQUEST

1. Fixing pins for saddle
2. Surcharge for piston motor Parker30
3. Surcharge for motor group 3 (Sz. 70-90)

1



2



3



The technical data, illustrations and features are indicative and do not commit the manufacturer.